

# EMRI kludges:

What they are, why they're important, and how to *end* them

---

Alvin Chua  
JPL-Caltech


22nd Capra Meeting  
CBPF, Rio de Janeiro  
17 June 2019



**Jet Propulsion Laboratory**  
California Institute of Technology

# Outline

- What's a kludge?
- An inventory of EMRI kludges
  - Analytic kludge (AK)
  - Numerical kludge (NK)
  - Augmented analytic kludge (AAK)
- Kludges in LISA preparatory science
- The EMRI data analysis problem
- Paving the way to surrogates
  - Existing pieces
  - Compression & interpolation
  - Strategies & coordination



# What's a kludge?

- Some particularly apt dictionary definitions:

*“Any construction or practice, typically **crude yet effective**, designed to solve a problem **temporarily or expediently**”*



# What's a kludge?

- Some particularly apt dictionary definitions:

*“Any construction or practice, typically  
crude yet effective, designed to solve  
a problem temporarily or expediently”*

*“An ill-assorted collection of  
poorly matching parts, forming  
a distressing whole”*



# What's a kludge?

- Some particularly apt dictionary definitions:

*“Any construction or practice, typically **crude yet effective**, designed to solve a problem **temporarily or expediently**”*

*“An ill-assorted collection of **poorly matching parts**, forming **a distressing whole**”*

*“A **badly written** or makeshift **piece of software**”*



# What's an EMRI kludge model?

- **if** Efficiency-oriented
  - Feasible for bulk use in data analysis algorithms
- **and** End-to-end
  - Source parameters  $\rightarrow$  trajectory  $\rightarrow$  orbit  $\rightarrow$  waveform  $\rightarrow$  detector response
- **and** Extensive
  - Describes generic Kerr orbits (intrinsic) & observer dependence (extrinsic)
- **and not** Fully relativistic
  - At least one component uses flat-space approximation
- **then** It's a kludge!

# What's an EMRI kludge model?

- **if** Efficiency-oriented
  - Feasible for bulk use in data analysis algorithms
- **and** End-to-end
  - Source parameters  $\rightarrow$  trajectory  $\rightarrow$  orbit  $\rightarrow$  waveform  $\rightarrow$  detector response
- **and** Extensive
  - Describes generic Kerr orbits (intrinsic) & observer dependence (extrinsic)
- **and not** Fully relativistic
  - At least one component uses flat-space approximation
- **then** It's a kludge!
- Disclaimer: This is my personal, completely non-standard definition
  - But really the only one you should use



# While we're defining terms...

- Waveform model:
  - Not efficiency-oriented + fully relativistic
- Template model:
  - Efficiency-oriented + end-to-end + extensive






# While we're defining terms...

- Waveform model:
  - Not efficiency-oriented + fully relativistic
- Template model:
  - Efficiency-oriented + end-to-end + extensive
- Surrogate model:
  - Efficiency-oriented + end-to-end + extensive + fully relativistic
  - i.e., a surrogate is a template model that is not a kludge
  - Can (probably will) be phenomenological, not self-consistent
  - Nomenclature is compatible with the NR ROM surrogates
- Approximant:
  - LIGO-speak for a surrogate



# Analytic kludge (AK)


- Barack & Cutler, 2004
- PN inspiral trajectory
  - Mixed-order fluxes for  $(p,e)$
  - Assume constant inclination
- Flat-space orbital evolution
  - Instantaneous Keplerian ellipses
  - Add PN precession



Barack & Cutler (2004)

# Analytic kludge (AK)


- Barack & Cutler, 2004
- PN inspiral trajectory
  - Mixed-order fluxes for  $(p,e)$
  - Assume constant inclination
- Flat-space orbital evolution
  - Instantaneous Keplerian ellipses
  - Add PN precession
- Flat-space waveform generation
  - Peters-Mathews decomposition
  - Hence quadrupolar
- Time-domain detector response
  - Long-wavelength approximation
  - Extended to t/f rigid-equal-arm TDI (Babak)



Barack & Cutler (2004)

# Analytic kludge (AK)


- Strengths:
  - Fast to generate at low eccentricity ( $< 0.5$ )
  - Fast to generate for long signals
  - Constructed from harmonic decomposition



Barack & Cutler (2004)

# Analytic kludge (AK)


- Strengths:
  - Fast to generate at low eccentricity ( $< 0.5$ )
  - Fast to generate for long signals
  - Constructed from harmonic decomposition
- Weaknesses:
  - Unphysical instantaneous frequencies
  - Limited performance at high eccentricity



Barack & Cutler (2004)

# Numerical kludge (NK)


- Babak et al., 2007
- PN inspiral trajectory
  - Mixed-order fluxes for (p,e,i)
  - Fit to adiabatic trajectories
- Curved-space orbital evolution
  - Instantaneous Kerr geodesics
  - Precession naturally included



Berry et al. (2019)

# Numerical kludge (NK)

- Babak et al., 2007
- PN inspiral trajectory
  - Mixed-order fluxes for (p,e,i)
  - Fit to adiabatic trajectories
- Curved-space orbital evolution
  - Instantaneous Kerr geodesics
  - Precession naturally included
- Flat-space waveform generation
  - Associate curved & flat coordinates
  - Several multipolar prescriptions
- Time-domain detector response
  - Only long-wavelength approximation
  - Needs LISA simulator for accurate response




Berry et al. (2019)



# Numerical kludge (NK)


- Strengths:
  - Good agreement with Teukolsky waveforms
  - Much faster than relativistic models
  - Easy to incorporate better trajectories



Babak et al. (2007)

# Numerical kludge (NK)


- Strengths:
  - Good agreement with Teukolsky waveforms
  - Much faster than relativistic models
  - Easy to incorporate better trajectories
- Weaknesses:
  - Multipole formalism is inefficient
  - Weak-field approximation is inaccurate at high eccentricity (see talk by Osburn)
  - No easy harmonic decomposition



Babak et al. (2007)

# Augmented analytic kludge (AAK)


- Chua & Gair, 2015
- PN inspiral trajectory
  - 3PN  $\mathcal{O}(e^6)$  fluxes for (p,e)
  - Assume constant inclination
  - Local fit to NK trajectories
- Flat-space orbital evolution
  - Map to Kerr instantaneous frequencies
  - Otherwise same as AK



Chua & Gair (2015)

# Augmented analytic kludge (AAK)


- Chua & Gair, 2015
- PN inspiral trajectory
  - 3PN  $\mathcal{O}(e^6)$  fluxes for (p,e)
  - Assume constant inclination
  - Local fit to NK trajectories
- Flat-space orbital evolution
  - Map to Kerr instantaneous frequencies
  - Otherwise same as AK
- Flat-space waveform generation
  - Same as AK
- Time-domain detector response
  - Same as AK



Chua & Gair (2015)

# Augmented analytic kludge (AAK)


- Strengths:
  - Same as AK
  - Good agreement with NK waveforms
  - Improved implementation
  - Actually being maintained by postdoc



Chua, Moore & Gair (2017)

# Augmented analytic kludge (AAK)

- Strengths:
  - Same as AK
  - Good agreement with NK waveforms
  - Improved implementation
  - Actually being maintained by postdoc
- Weaknesses:
  - Limited performance at high eccentricity
  - Frequency map ill-defined at plunge



Chua, Moore & Gair (2017)

# EMRI Kludge Suite


- Software suite with all 3 kludges & common interface
  - Latest version: 0.4.2
  - NK not being maintained
  - AK only being maintained until end of LDC-1






# EMRI Kludge Suite

- Software suite with all 3 kludges & common interface
  - Latest version: 0.4.2
  - NK not being maintained
  - AK only being maintained until end of LDC-1
- Installation
  - Clone from: [github.com/alvincjk/EMRI\\_Kludge\\_Suite](https://github.com/alvincjk/EMRI_Kludge_Suite)
  - Needs GSL & FFTW libraries
  - Python wrapper available for some executables



# EMRI Kludge Suite


- Software suite with all 3 kludges & common interface
  - Latest version: 0.4.2
  - NK not being maintained
  - AK only being maintained until end of LDC-1
- Installation
  - Clone from: [github.com/alvincjk/EMRI\\_Kludge\\_Suite](https://github.com/alvincjk/EMRI_Kludge_Suite)
  - Needs GSL & FFTW libraries
  - Python wrapper available for some executables
- Usage
  - Executables in ./bin: Waveforms (all models), TDIs (AK/AAK), phases (AAK)
  - Template files in ./examples: Source/waveform parameters, model settings
  - Import Python module AAKwrapper, example usage in AAKdemo.py
  - Caveat utilitor: Limited domain validation & error handling



# EMRI Kludge Suite


Model	Trajectory	Orbit	Waveform/response	Accuracy	Speed
AK	<ul style="list-style-type: none"><li>- Mixed-order PN fluxes</li></ul>	<ul style="list-style-type: none"><li>- Evolving Keplerian ellipses</li></ul>	<ul style="list-style-type: none"><li>- Peters-Mathews approximation to quadrupole</li><li>- Rigid-equal-arm approximation (TDIs)</li></ul>	<ul style="list-style-type: none"><li>- Instantaneous frequencies too high</li><li>- Schwarzschild plunge handling</li><li>- Qualitative use only</li></ul>	<ul style="list-style-type: none"><li>- Fast, but less speedup over NK for shorter waveforms or more eccentric orbits</li></ul>
AAK	<ul style="list-style-type: none"><li>- 3PN <math>O(e^6)</math> fluxes</li><li>- Locally fitted to NK trajectories</li></ul>	<ul style="list-style-type: none"><li>- Evolving Keplerian ellipses</li><li>- Instantaneous frequencies mapped to Kerr</li></ul>	<ul style="list-style-type: none"><li>- Peters-Mathews approximation to quadrupole</li><li>- Rigid-equal-arm approximation (TDIs)</li></ul>	<ul style="list-style-type: none"><li>- Phase-accurate w.r.t. NK waveforms, for 2-6 months</li><li>- Approximate Kerr plunge handling</li></ul>	<ul style="list-style-type: none"><li>- Same as AK, but slightly faster due to streamlining</li></ul>
NK	<ul style="list-style-type: none"><li>- Mixed-order PN fluxes</li><li>- Fitted to adiabatic trajectories</li></ul>	<ul style="list-style-type: none"><li>- Evolving Kerr geodesics</li></ul>	<ul style="list-style-type: none"><li>- Quadrupole</li><li>- Long-wavelength approximation (<math>h_{l,l}</math>)</li></ul>	<ul style="list-style-type: none"><li>- Phase-accurate w.r.t. adiabatic waveforms, down to 2-3 <math>r_{\text{ISCO}}</math></li><li>- Kerr plunge handling</li></ul>	<ul style="list-style-type: none"><li>- Order of magnitude slower than AK/AAK on average</li></ul>

# Kludges in LISA preparatory science




- Data analysis
  - Synthetic data sets
    - MLDCs, 2006-2011 (using AK); LDCs, 2018-present (transitioning from AK to AAK)
  - Search algorithms
    - Babak, Gair & Porter, 2009 + Cornish, 2011 + Wang, Shang & Babak, 2012 + several others (all using simplified, kludge-informed, time-frequency techniques)
  - Inference algorithms
    - Ali et al., 2012 (short data segments); not much else (even kludges are still too slow)

# Kludges in LISA preparatory science




- Data analysis
  - Synthetic data sets
    - MLDCs, 2006-2011 (using AK); LDCs, 2018-present (transitioning from AK to AAK)
  - Search algorithms
    - Babak, Gair & Porter, 2009 + Cornish, 2011 + Wang, Shang & Babak, 2012 + several others (all using simplified, kludge-informed, time-frequency techniques)
  - Inference algorithms
    - Ali et al., 2012 (short data segments); not much else (even kludges are still too slow)
  - Degeneracies & confusion
    - Chua & Cutler, in prep. (mapping out the overlap surface); Barack & Cutler, 2004 + Karnesis, Chua & Babak, in prep. (unresolvable EMRI background)
  - Systematics (theoretical errors)
    - Huerta & Gair, 2009 (effect of conservative corrections); Berry et al., 2016 (effect of resonances); Chua et al., in prep. (error marginalization)

# Kludges in LISA preparatory science



- Mission performance
  - Detection rates
    - Gair et al., 2004 (using AK); Babak et al., 2017 + several other reports/proposals (*still* using AK); **Chua, Moore & Gair, 2017** (using AAK)
  - Parameter estimation precision (statistical errors)
    - Barack & Cutler, 2004 + Babak et al., 2017 + several other reports/proposals (all using AK)

# Kludges in LISA preparatory science




- Mission performance
  - Detection rates
    - Gair et al., 2004 (using AK); Babak et al., 2017 + several other reports/proposals (*still* using AK); Chua, Moore & Gair, 2017 (using AAK)
  - Parameter estimation precision (statistical errors)
    - Barack & Cutler, 2004 + Babak et al., 2017 + several other reports/proposals (all using AK)
- Science applications
  - Fundamental physics (tests of gravity)
    - Glampedakis & Babak, 2006 + Barack & Cutler, 2007 + Chua et al., 2018 (generic Kerr deviations); Canizares, Gair & Sopuerta, 2012 (dynamical Chern-Simons); possibly others
  - Astrophysics & cosmology
    - Sesana et al., 2008 (WD EMRIs); Han & Chen, 2019 (b-EMRIs);  
surprisingly not much else (heuristic analysis, or just use cited rates/precision)




# Outline (redux)

- What's a kludge?
- An inventory of EMRI kludges
  - Analytic kludge (AK)
  - Numerical kludge (NK)
  - Augmented analytic kludge (AAK)
- Kludges in LISA preparatory science
- The EMRI data analysis problem
- Paving the way to surrogates
  - Existing pieces
  - Compression & interpolation
  - Strategies & coordination



# Key features of LISA data analysis


- Problem 0: Instrument/noise model
  - Complicated instrument response
  - Non-stationary noise
  - Gaps & glitches



N. Douillet

# Key features of LISA data analysis


- Problem 0: Instrument/noise model
  - Complicated instrument response
  - Non-stationary noise
  - Gaps & glitches
- Problem 1: Signal confusion
  - Many signals overlap in time/frequency: Galactic binaries + SMBH mergers + EMRIs
  - Cannot just subtract then move on
  - Global-solution algorithm is required
  - Not practical to do fully simultaneous fit



Arnaud et al. (2007)


# Key features of LISA data analysis

- Problem 2: Global search
  - Parameter space can be massive:  
Large dimensionality & information volume
  - Credible regions can be very localized
  - Stochastic search algorithms are required
  - Search is hierarchical & needs multiple passes



# Key features of LISA data analysis

- Problem 2: Global search
  - Parameter space can be massive:  
Large dimensionality & information volume
  - Credible regions can be very localized
  - Stochastic search algorithms are required
  - Search is hierarchical & needs multiple passes
- Problem 3: Modeling accuracy
  - Bias when theoretical error > statistical error
  - Only for strong-field, high-SNR sources
  - Most interesting, but most difficult to model
  - Need to understand errors for waveforms, minimize loss of accuracy for templates



Cutler & Vallisneri (2007)

# The EMRI data analysis problem

- Galactic binaries
  - Confusion: Severe (resolvable + background)
  - Search: Low SNR & many signals to resolve, but templates are inexpensive
  - Modeling: No problem



# The EMRI data analysis problem

- Galactic binaries
  - Confusion: Severe (resolvable + background)
  - Search: Low SNR & many signals to resolve, but templates are inexpensive
  - Modeling: No problem
- SMBH mergers
  - Confusion: None
  - Search: Expensive templates & localized, but high SNR & fewer signals to find
  - Modeling: Difficult (NR)





# The EMRI data analysis problem

- Galactic binaries
  - Confusion: Severe (resolvable + background)
  - Search: Low SNR & many signals to resolve, but templates are inexpensive
  - Modeling: No problem
- SMBH mergers
  - Confusion: None
  - Search: Expensive templates & localized, but high SNR & fewer signals to find
  - Modeling: Difficult (NR)
- EMRIs
  - Confusion: Maybe (possible degeneracies, uncertain event rates)
  - Search: Expensive templates, highly localized, moderate SNR, possibly many signals
  - Modeling: Difficult (SF)



# Will kludges be good enough?

- In terms of speed
  - Template cost:  $> 10^2$  s (!)
  - Time samples:  $> 10^7$  (4 years  $\times$  0.1 Hz)
  - Overlap calls:  $10^9$ - $10^{30}$  (!!)
  - Prohibitive for search (without sacrificing accuracy)
  - Barely OK for inference



ORNL

# Will kludges be good enough?

- In terms of speed
  - Template cost:  $> 10^2$  s (!)
  - Time samples:  $> 10^7$  (4 years  $\times$  0.1 Hz)
  - Overlap calls:  $10^9$ - $10^{30}$  (!!)
  - Prohibitive for search (without sacrificing accuracy)
  - Barely OK for inference
- In terms of accuracy
  - Assume overlaps of 0.97 with true signals
  - Barely OK for search: Lose up to half of signals (Chua, Moore & Gair, 2017)
  - Nowhere near good enough for inference



ORNL

# Will kludges be good enough?


- In terms of speed
  - Template cost:  $> 10^2$  s (!)
  - Time samples:  $> 10^7$  (4 years  $\times$  0.1 Hz)
  - Overlap calls:  $10^9$ - $10^{30}$  (!!)
  - Prohibitive for search (without sacrificing accuracy)
  - Barely OK for inference
- In terms of accuracy
  - Assume overlaps of 0.97 with true signals
  - Barely OK for search: Lose up to half of signals (Chua, Moore & Gair, 2017)
  - Nowhere near good enough for inference
- Need for **surrogates & algorithms tailored to EMRI problem**
  - Let's leave kludges & traditional data analysis approaches behind



ORNL

# Surrogates: Existing pieces


- Trajectory & orbit
  - PN flux-based (see talks by Isoyama, Munna)
  - Teukolsky flux-based (see talk by Hughes)
  - SF-based (van de Meent & Warburton, 2018; see also talk by Osburn)



van de Meent & Warburton (2018)

# Surrogates: Existing pieces

- Trajectory & orbit
  - PN flux-based (see talks by Isoyama, Munna)
  - Teukolsky flux-based (see talk by Hughes)
  - SF-based (van de Meent & Warburton, 2018; see also talk by Osburn)
- Waveform
  - Teukolsky snapshots
  - Adiabatic (see talks by Hughes, Isoyama)
- Response
  - Approximate TDI (Babak; Marsat & Baker, 2018)



Drasco (2009)


# Surrogates: Compression & interpolation

- ROM surrogates (Field et al., 2014)
  - Construct reduced basis for signal space
  - Only valid over restricted parameter domain
  - Resultant template model is fast & accurate
  - May be viable for EMRIs with smart representation

$$h(\theta) = \sum_i \alpha_i(\theta) e_i \equiv \alpha(\theta)$$

# Surrogates: Compression & interpolation

- ROM surrogates (Field et al., 2014)
  - Construct reduced basis for signal space
  - Only valid over restricted parameter domain
  - Resultant template model is fast & accurate
  - May be viable for EMRIs with smart representation
- ROMAN (Chua, Galley & Vallisneri, 2019)
  - Same basis & domain as ROM surrogates
  - Comparable speed & accuracy
  - More general, connects directly to data analysis
  - Shows utility of neural-network interpolation (dimensionality, derivatives, etc.)



Chua, Galley & Vallisneri (2019)



# Surrogates: Strategies & coordination


- Work in time-frequency domain
  - Lossless representation: STFT, wavelets, etc.
  - Admits native generation & data analysis
  - Can deal with non-stationarity & gaps
  - Best suited to nature of EMRIs & LISA

$$h(\tau, \omega) = \int dt h(t) W(t - \tau) e^{-i\omega t}$$

$$h(a, b) = \frac{1}{\sqrt{a}} \int dt h(t) \psi\left(\frac{t - b}{a}\right)$$

# Surrogates: Strategies & coordination


- Work in time-frequency domain
  - Lossless representation: STFT, wavelets, etc.
  - Admits native generation & data analysis
  - Can deal with non-stationarity & gaps
  - Best suited to nature of EMRIs & LISA
- Compress & interpolate everything
  - e.g. Map geodesics to Teukolsky amplitudes
- Incorporate parallelization from the start
  - e.g. Native GPU implementations



Chua et al. (in prep.)

# Surrogates: Strategies & coordination

- Work in time-frequency domain
  - Lossless representation: STFT, wavelets, etc.
  - Admits native generation & data analysis
  - Can deal with non-stationarity & gaps
  - Best suited to nature of EMRIs & LISA
- Compress & interpolate everything
  - e.g. Map geodesics to Teukolsky amplitudes
- Incorporate parallelization from the start
  - e.g. Native GPU implementations
- Identify & add important missing pieces
  - Transient resonances
  - Tidal resonances? (see talk by Bonga)
  - Secondary spin? (see talk by Witzany)



Berry et al. (2016)

# Surrogates: Strategies & coordination

- LSG WP 1.8.3: Efficient EMRI models
  - Kludges & related tools for LDCs
  - Fast LISA response for EMRIs
  - Reduced-representation templates
  - Fast transient resonance models
  - Fast SF trajectories
  - Modern computational techniques
- Also WPs 1.2.1 (Pound), 1.2.2 (Warburton), 1.2.3 (Brito)




# Surrogates: Strategies & coordination

- LSG WP 1.8.3: Efficient EMRI models
  - Kludges & related tools for LDCs
  - Fast LISA response for EMRIs
  - Reduced-representation templates
  - Fast transient resonance models
  - Fast SF trajectories
  - Modern computational techniques
- Also WPs 1.2.1 (Pound), 1.2.2 (Warburton), 1.2.3 (Brito)
- Calling for expressions of interest/commitment
  - No need to be full or even associate LISA member
  - More at: [tinyurl.com/emri-templates](https://tinyurl.com/emri-templates)



# Summary

- EMRI kludge models are efficiency-oriented, end-to-end, extensive, but not fully relativistic
- Kludges have fulfilled their purpose of scoping out LISA data analysis issues; they will still be relevant in the near future
- We now have the pieces to construct surrogate models that are more directly informed by perturbation theory
- These will be tailored to LISA data analysis requirements; modern computational techniques will improve both speed & accuracy



# References

- A. J. K. Chua & J. R. Gair, Improved analytic extreme-mass-ratio inspiral model for scoping out eLISA data analysis, *Class. Quantum Grav.* 32, 232002 (2015).
- A. J. K. Chua, Augmented kludge waveforms and Gaussian process regression for EMRI data analysis, *J. Phys.: Conf. Ser.* 716, 012028 (2016).
- A. J. K. Chua, C. J. Moore & J. R. Gair, Augmented kludge waveforms for detecting extreme-mass-ratio inspirals, *Phys. Rev. D* 96, 044005 (2017).
- C. J. Moore, A. J. K. Chua & J. R. Gair, Gravitational waves from extreme mass ratio inspirals around bumpy black holes, *Class. Quantum Grav.* 34, 195009 (2017).
- A. J. K. Chua et al., Towards a framework for testing general relativity with extreme-mass-ratio-inspiral observations, *Mon. Notices Royal Astron. Soc.* 478, 28 (2018).
- A. J. K. Chua, C. R. Galley & M. Vallisneri, Reduced-order modeling with artificial neurons for gravitational-wave inference, *Phys. Rev. Lett.* 122, 211101 (2019).